

屋内照明器具特性	
品番 (品名)	XLGB1106
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176259(0)DR1
BZ分類	BZ4/2.3/BZ5

器具効率	63%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	61%	室指数	照明率 (×0.01)																ZCM	
保守率	良	0.67	0.6	3.7	3.0	2.5	2.2	3.6	3.0	2.5	2.2	3.5	2.9	2.5	2.2	3.3	2.8	2.4	2.2	2.0
	中	0.63	0.8	4.3	3.6	3.1	2.8	4.2	3.6	3.1	2.8	4.0	3.5	3.1	2.8	3.8	3.4	3.0	2.7	2.6
	否	0.56	1.0	4.7	4.0	3.6	3.2	4.6	4.0	3.5	3.2	4.4	3.9	3.5	3.2	4.2	3.8	3.4	3.1	3.0
			1.25	5.0	4.5	4.0	3.7	4.9	4.4	4.0	3.6	4.7	4.3	3.9	3.6	4.5	4.1	3.8	3.6	3.4
下方投影面積		cm ²	1.5	5.3	4.8	4.3	4.0	5.2	4.7	4.3	4.0	5.0	4.5	4.2	3.9	4.8	4.4	4.1	3.9	3.7
等価発光面積		cm ²	2.0	5.6	5.2	4.8	4.5	5.5	5.1	4.7	4.5	5.3	4.9	4.6	4.4	5.1	4.8	4.5	4.3	4.1
取付高さ	器具間隔最大限		2.5	5.8	5.4	5.1	4.8	5.7	5.4	5.1	4.8	5.5	5.2	4.9	4.7	5.3	5.0	4.8	4.6	4.4
	横方向 (A)	縦方向 (B)	3.0	6.0	5.6	5.4	5.1	5.9	5.6	5.3	5.0	5.7	5.4	5.2	5.0	5.5	5.2	5.0	4.9	4.7
Hm	1.00Hm	1.00Hm	4.0	6.2	5.9	5.7	5.4	6.1	5.8	5.6	5.4	5.9	5.6	5.5	5.3	5.7	5.5	5.3	5.2	5.0
			5.0	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.6	6.0	5.8	5.6	5.5	5.8	5.6	5.5	5.4	5.2
			7.0	6.4	6.3	6.1	6.0	6.3	6.2	6.0	5.9	6.1	6.0	5.9	5.8	5.9	5.8	5.7	5.6	5.4
			10.0	6.5	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.2	6.1	6.0	6.0	6.0	6.0	5.9	5.8	5.6

