

屋内照明器具特性

品番 (品名)	L G W 5 0 6 2 0 F	
光源	LDA4N- G/ E/ W ×2	485.0 lm
管理番号	K0168636 (0) DB 1	
B Z 分類	B Z 6	

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		10 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		54 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			Z C M	
保守率	良	0.63	0.6	33	24	19	15	31	23	19	15	29	22	18	14	26	21	17	14	12	
	中	0.6	0.8	38	30	25	21	37	29	24	21	34	27	23	20	31	26	22	19	16	
	否	0.56	1.0	42	35	29	25	41	34	29	25	37	31	27	24	34	29	25	22	20	
			1.25	46	39	34	30	44	38	33	29	41	35	31	28	37	33	29	26	23	
下方投影面積	c m ²		1.5	49	42	37	33	47	41	36	32	43	38	34	31	40	35	32	29	26	
	等価発光面積		c m ²	2.0	52	47	42	38	50	45	41	37	47	42	39	35	43	39	36	34	30
取付高さ	器具間隔最大限		2.5	55	50	46	42	53	48	44	41	49	45	42	39	45	42	39	37	33	
	横方向 (A)	縦方向 (B)	3.0	57	52	48	45	54	50	47	44	51	47	44	41	47	44	42	39	35	
H m	1.34 H m	1.34 H m	4.0	59	55	52	49	57	53	50	48	53	50	47	45	49	47	45	43	39	
			5.0	60	57	54	52	58	55	53	50	54	52	50	48	51	49	47	45	41	
			7.0	62	59	57	55	60	58	56	54	56	54	52	51	52	51	49	48	44	
			10.0	63	61	60	58	61	60	58	56	58	56	55	53	54	53	52	51	46	

