

屋内照明器具特性

品番 (品名) **LGB15392**

光源 **LLD2020MLCB1 ×1** **460.0lm**

管理番号 **K0175668(1)DR1**

BZ分類 **BZ1**

器具効率	84%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	84%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	74	70	67	65	73	69	67	65	72	69	67	65	71	68	66	65	64	
	中 0.63	0.8	78	74	72	70	77	74	72	70	76	73	71	70	75	73	71	69	69	
	否 0.56	1.0	81	77	75	73	80	77	75	73	79	76	74	73	78	75	74	72	71	
下方投影面積	cm ²	1.25	83	80	78	76	82	79	77	76	81	78	77	75	79	78	76	75	74	
		1.5	84	81	79	78	83	81	79	77	82	80	78	77	81	79	78	76	75	
等価発光面積	cm ²	2.0	86	84	82	80	85	83	81	80	83	82	80	79	82	81	80	79	77	
		2.5	87	85	83	82	86	84	83	82	84	83	82	81	83	82	81	80	78	
取付高さ	器具間隔最大限		3.0	87	86	84	83	86	85	84	83	85	84	83	82	83	82	82	81	79
	横方向 (A)	縦方向 (B)	4.0	88	87	86	85	87	86	85	84	86	85	84	83	84	83	83	82	80
Hm	0.47Hm	0.47Hm	5.0	89	88	87	86	88	87	86	85	86	85	85	84	84	84	83	83	81
			7.0	89	88	88	87	88	88	87	86	86	86	85	85	85	84	84	84	82
			10.0	90	89	89	88	89	88	88	87	87	86	86	86	85	85	85	84	82

