

屋内照明器具特性

品番 (品名) **LGB15392**

光源 **LLD2020LCE1 x1** **460.0 lm**

管理番号 **K0175659 (1) DR1**

BZ分類 **BZ1**

器具効率	86%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	86%	床		10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	76	71	69	67	75	71	69	67	74	71	68	67	73	70	68	66	66	
	中 0.63	0.8	80	76	74	72	79	76	73	72	78	75	73	71	77	75	73	71	70	
	否 0.56	1.0	83	79	77	75	82	79	77	75	81	78	76	75	80	77	76	74	73	
下方投影面積	cm ²	1.25	85	82	80	78	84	81	79	78	83	80	79	77	81	80	78	77	76	
		1.5	86	84	81	80	85	83	81	80	84	82	80	79	83	81	80	78	77	
等価発光面積	cm ²	2.0	88	86	84	82	87	85	83	82	86	84	83	81	84	83	82	81	79	
		2.5	89	87	86	84	88	86	85	84	86	85	84	83	85	84	83	82	80	
取付高さ	器具間隔最大限		3.0	90	88	87	85	89	87	86	85	87	86	85	84	85	85	84	83	81
	横方向 (A)	縦方向 (B)	4.0	90	89	88	87	90	88	87	86	88	87	86	85	86	85	85	84	82
Hm	0.42Hm	0.42Hm	5.0	91	90	89	88	90	89	88	87	88	88	87	86	87	86	85	83	
			7.0	91	91	90	89	91	90	89	89	89	88	88	87	87	87	86	84	
			10.0	92	91	91	90	91	90	90	90	89	89	88	88	87	87	86	84	

