

屋内照明器具特性	
品番 (品名)	LGW50632F
光源	LDA7N-G/E/W ×2 810.0 lm
管理番号	K0169056(0)DB1
BZ分類	BZ6

器具効率	53%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	8%	床	10%				10%				10%				10%				0%	
下方光束	45%	室指数	照明率 (×0.01)																ZCM	
保守率	良	0.63	0.6	2.7	2.0	1.6	1.3	2.6	1.9	1.5	1.2	2.3	1.8	1.4	1.2	2.2	1.7	1.4	1.1	1.0
	中	0.6	0.8	3.2	2.5	2.1	1.7	3.0	2.4	2.0	1.7	2.8	2.3	1.9	1.6	2.6	2.1	1.8	1.6	1.4
	否	0.56	1.0	3.5	2.9	2.4	2.1	3.3	2.8	2.4	2.0	3.1	2.6	2.2	1.9	2.8	2.4	2.1	1.9	1.6
			1.25	3.8	3.2	2.8	2.4	3.6	3.1	2.7	2.4	3.3	2.9	2.6	2.3	3.1	2.7	2.4	2.2	1.9
下方投影面積		cm ²	1.5	4.0	3.5	3.1	2.7	3.9	3.4	3.0	2.7	3.5	3.1	2.8	2.5	3.3	2.9	2.6	2.4	2.1
等価発光面積		cm ²	2.0	4.3	3.8	3.5	3.1	4.1	3.7	3.4	3.1	3.8	3.5	3.2	2.9	3.5	3.2	3.0	2.8	2.5
取付高さ	器具間隔最大限		2.5	4.5	4.1	3.8	3.5	4.3	4.0	3.6	3.4	4.0	3.7	3.4	3.2	3.7	3.5	3.2	3.0	2.7
	横方向 (A)	縦方向 (B)	3.0	4.7	4.3	4.0	3.7	4.5	4.1	3.9	3.6	4.2	3.9	3.6	3.4	3.9	3.6	3.4	3.2	2.9
Hm	1.33Hm	1.33Hm	4.0	4.8	4.5	4.3	4.0	4.7	4.4	4.1	3.9	4.3	4.1	3.9	3.7	4.0	3.9	3.7	3.5	3.2
			5.0	5.0	4.7	4.5	4.2	4.8	4.5	4.3	4.1	4.5	4.3	4.1	3.9	4.2	4.0	3.9	3.7	3.4
			7.0	5.1	4.9	4.7	4.5	4.9	4.7	4.6	4.4	4.6	4.5	4.3	4.2	4.3	4.2	4.1	4.0	3.6
			10.0	5.2	5.1	4.9	4.8	5.0	4.9	4.8	4.6	4.7	4.6	4.5	4.4	4.4	4.3	4.3	4.2	3.8

