

屋内照明器具特性

品番 (品名) **LGB15392**

光源 **LLD3020LCB1 x1** **795.0 l m**

管理番号 **K0175657 (1) DR1**

BZ分類 **BZ1**

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	75 %		壁	10 %				10 %				10 %				10 %				0 %
		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X 0.01)																ZCM	
保守率	良 0.67	0.6	67	63	60	59	66	63	60	59	65	62	60	59	64	62	60	58	58	
	中 0.63	0.8	70	67	65	63	70	67	65	63	69	66	64	63	68	66	64	63	62	
	否 0.56	1.0	73	70	68	66	72	69	67	66	71	69	67	66	70	68	66	65	64	
下方投影面積	c m ²	1.25	75	72	70	68	74	72	70	68	73	71	69	68	72	70	69	67	67	
		1.5	76	73	72	70	75	73	71	70	74	72	71	69	73	71	70	69	68	
等価発光面積	c m ²	2.0	77	75	74	73	77	75	73	72	75	74	73	72	74	73	72	71	70	
		2.5	78	77	75	74	77	76	75	74	76	75	74	73	75	74	73	72	71	
取付高さ	器具間隔最大限		3.0	79	77	76	75	78	77	76	75	76	75	75	74	75	74	74	73	71
H m	0.43 H m	0.43 H m	4.0	79	78	77	77	79	78	77	76	77	76	76	75	76	75	74	74	72
			5.0	80	79	78	77	79	78	78	77	78	77	76	76	76	76	76	75	75
			7.0	80	80	79	79	80	79	78	78	78	77	77	77	76	76	76	75	73
			10.0	81	80	80	79	80	79	79	79	78	78	78	77	77	76	76	76	74

