

# 屋内照明器具特性

品番 (品名)	LGB15392														
光源	LLD2000MLCE1 ×1 531.0 lm														
管理番号	K0175665 (1) DR1														
BZ分類	BZ1														

器具効率	53%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	53%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.67	0.6	41	37	35	33	41	37	35	33	40	37	35	33	39	37	35	33	33
	中	0.63	0.8	45	42	40	38	45	42	39	38	44	41	39	38	43	41	39	38	37
	否	0.56	1.0	48	45	42	41	47	44	42	41	46	44	42	41	45	43	42	40	40
			1.25	50	47	45	43	49	47	45	43	48	46	44	43	47	45	44	43	42
下方投影面積			1.5	51	49	47	45	50	48	46	45	49	47	46	45	48	47	46	44	44
			2.0	52	51	49	48	52	50	49	48	51	49	48	47	50	49	48	47	46
取付高さ	器具間隔最大限		2.5	53	52	50	49	53	51	50	49	52	50	49	49	51	50	49	48	47
	横方向 (A)	縦方向 (B)	3.0	54	53	51	50	53	52	51	50	52	51	50	50	51	50	50	49	48
Hm	0.68Hm	0.68Hm	4.0	55	54	53	52	54	53	52	52	53	52	51	51	52	51	51	50	49
			5.0	55	54	54	53	55	54	53	52	53	53	52	52	52	52	51	51	50
			7.0	56	55	54	54	55	54	54	53	54	53	53	53	53	52	52	52	50
			10.0	56	56	55	55	55	55	55	54	54	54	54	53	53	53	53	52	51

