

屋内照明器具特性	
品番 (品名)	LGB15392
光源	LLD4000MLCE1 ×1 845.0 l m
管理番号	K0175661 (1) DR 1
BZ分類	BZ1

器具効率	46 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	46 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.6	3.2	3.0	2.9	3.5	3.2	3.0	2.9	3.5	3.2	3.0	2.9	3.4	3.1	3.0	2.9	2.8
	中	0.63	0.8	3.9	3.6	3.4	3.3	3.9	3.6	3.4	3.3	3.8	3.5	3.4	3.2	3.7	3.5	3.4	3.2	3.2
	否	0.56	1.0	4.1	3.8	3.7	3.5	4.1	3.8	3.6	3.5	4.0	3.8	3.6	3.5	3.9	3.7	3.6	3.5	3.4
			1.25	4.3	4.0	3.9	3.7	4.2	4.0	3.9	3.7	4.1	4.0	3.8	3.7	4.1	3.9	3.8	3.7	3.6
下方投影面積		c m ²	1.5	4.4	4.2	4.0	3.9	4.3	4.2	4.0	3.9	4.2	4.1	4.0	3.9	4.2	4.0	3.9	3.8	3.8
等価発光面積		c m ²	2.0	4.5	4.4	4.2	4.1	4.5	4.3	4.2	4.1	4.4	4.3	4.1	4.1	4.3	4.2	4.1	4.0	3.9
取付高さ	器具間隔最大限		2.5	4.6	4.5	4.4	4.3	4.6	4.4	4.3	4.2	4.5	4.4	4.3	4.2	4.4	4.3	4.2	4.1	4.1
	横方向 (A)	縦方向 (B)	3.0	4.7	4.5	4.4	4.4	4.6	4.5	4.4	4.3	4.5	4.4	4.3	4.3	4.4	4.3	4.3	4.2	4.1
H m	0.68 H m	0.68 H m	4.0	4.7	4.6	4.6	4.5	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.4	4.5	4.4	4.4	4.3	4.2
			5.0	4.8	4.7	4.6	4.6	4.7	4.6	4.6	4.5	4.6	4.6	4.5	4.5	4.5	4.5	4.4	4.4	4.3
			7.0	4.8	4.8	4.7	4.7	4.8	4.7	4.7	4.6	4.7	4.6	4.6	4.5	4.6	4.5	4.5	4.5	4.3
			10.0	4.8	4.8	4.8	4.7	4.8	4.8	4.7	4.7	4.7	4.7	4.6	4.6	4.6	4.6	4.5	4.5	4.4

