

屋内照明器具特性

品番 (品名) **LGB15392**

光源 **LLD3020MLCE1 ×1** 795.0 lm

管理番号 **K0175663 (1) DR1**

BZ分類 **BZ1**

器具効率	77%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	77%	床		10%				10%				10%				10%				0%
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	68	64	61	59	67	63	61	59	66	63	61	59	65	63	61	59	59	
	中 0.63	0.8	71	68	66	64	71	68	66	64	70	67	65	64	69	67	65	64	63	
	否 0.56	1.0	74	71	69	67	73	70	68	67	72	70	68	66	71	69	67	66	65	
下方投影面積	cm ²	1.25	76	73	71	69	75	73	71	69	74	72	70	69	73	71	70	68	67	
		1.5	77	75	73	71	76	74	72	71	75	73	72	70	74	72	71	70	69	
等価発光面積	cm ²	2.0	78	77	75	74	78	76	75	73	76	75	74	73	75	74	73	72	71	
		2.5	79	78	76	75	79	77	76	75	77	76	75	74	76	75	74	73	72	
取付高さ	器具間隔最大限		3.0	80	79	77	76	79	78	77	76	78	77	76	75	76	75	75	74	73
Hm	横方向 (A)	縦方向 (B)	4.0	81	80	79	78	80	79	78	77	78	78	77	76	77	76	76	75	73
	0.44Hm	0.44Hm	5.0	81	80	79	79	80	80	79	78	79	78	78	77	77	77	76	76	74
			7.0	82	81	80	80	81	80	80	79	79	79	78	78	78	77	77	77	75
			10.0	82	82	81	81	81	81	80	80	80	79	79	79	78	78	77	77	75

