

屋内照明器具特性	
品番 (品名)	LGB15392
光源	LLD2000MLCB1 ×1 531.0 l m
管理番号	K0175666 (1) DR 1
BZ分類	BZ1

器具効率	54 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
			床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 (X0.01)																ZCM	
下方光束	54 %																			
保守率	良 中 否 0.67 0.63 0.56	0.6	4.2	3.8	3.6	3.4	4.2	3.8	3.6	3.4	4.1	3.8	3.5	3.4	4.0	3.7	3.5	3.4	3.3	
		0.8	4.6	4.3	4.0	3.9	4.6	4.2	4.0	3.9	4.5	4.2	4.0	3.8	4.4	4.1	4.0	3.8	3.8	
		1.0	4.8	4.5	4.3	4.2	4.8	4.5	4.3	4.1	4.7	4.5	4.3	4.1	4.6	4.4	4.2	4.1	4.0	
		1.25	5.0	4.8	4.6	4.4	5.0	4.7	4.6	4.4	4.9	4.7	4.5	4.4	4.8	4.6	4.5	4.4	4.3	
下方投影面積	c m ²	1.5	5.2	4.9	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.6	4.9	4.8	4.6	4.5	4.4	
		2.0	5.3	5.1	5.0	4.9	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.8	5.1	4.9	4.8	4.7	4.7	
取付高さ	器具間隔最大限		2.5	5.4	5.3	5.1	5.0	5.4	5.2	5.1	5.0	5.3	5.1	5.0	4.9	5.2	5.1	5.0	4.9	
	横方向 (A)	縦方向 (B)	3.0	5.5	5.4	5.2	5.1	5.4	5.3	5.2	5.1	5.3	5.2	5.1	5.0	5.2	5.1	5.0	4.9	
H m	0.67 H m	0.67 H m	4.0	5.6	5.5	5.4	5.3	5.5	5.4	5.3	5.2	5.4	5.3	5.2	5.2	5.3	5.2	5.1	5.0	
			5.0	5.6	5.5	5.4	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.3	5.3	5.3	5.2	5.0	
			7.0	5.7	5.6	5.5	5.5	5.6	5.5	5.5	5.4	5.5	5.4	5.4	5.4	5.4	5.3	5.3	5.1	
			10.0	5.7	5.7	5.6	5.6	5.6	5.6	5.5	5.5	5.5	5.5	5.5	5.4	5.4	5.4	5.3	5.2	

