

屋内照明器具特性	
品番 (品名)	LGB15392
光源	LLD4000MLCB1 ×1 845.0 lm
管理番号	K0175662(1)DR1
BZ分類	BZ1

器具効率	44%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	44%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	3.4	3.1	2.9	2.8	3.4	3.1	2.9	2.8	3.3	3.1	2.9	2.7	3.3	3.0	2.9	2.7	2.7
	中	0.63	0.8	3.7	3.5	3.3	3.1	3.7	3.4	3.3	3.1	3.6	3.4	3.2	3.1	3.6	3.4	3.2	3.1	3.1
	否	0.56	1.0	3.9	3.7	3.5	3.4	3.9	3.7	3.5	3.4	3.8	3.6	3.5	3.4	3.7	3.6	3.4	3.3	3.3
			1.25	4.1	3.9	3.7	3.6	4.1	3.9	3.7	3.6	4.0	3.8	3.7	3.6	3.9	3.8	3.6	3.5	3.5
下方投影面積			1.5	4.2	4.0	3.9	3.8	4.2	4.0	3.8	3.7	4.1	3.9	3.8	3.7	4.0	3.9	3.8	3.7	3.6
	等価発光面積		2.0	4.3	4.2	4.1	4.0	4.3	4.2	4.0	3.9	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.9	3.8
取付高さ	器具間隔最大限		2.5	4.4	4.3	4.2	4.1	4.4	4.3	4.2	4.1	4.3	4.2	4.1	4.0	4.2	4.1	4.0	4.0	3.9
	横方向 (A)	縦方向 (B)	3.0	4.5	4.4	4.3	4.2	4.4	4.3	4.2	4.2	4.3	4.2	4.2	4.1	4.2	4.2	4.1	4.1	4.0
Hm	0.68Hm	0.68Hm	4.0	4.5	4.4	4.4	4.3	4.5	4.4	4.3	4.3	4.4	4.3	4.3	4.2	4.3	4.2	4.2	4.1	
			5.0	4.6	4.5	4.4	4.4	4.5	4.5	4.4	4.3	4.4	4.4	4.3	4.3	4.3	4.3	4.3	4.2	4.1
			7.0	4.6	4.6	4.5	4.5	4.6	4.5	4.5	4.4	4.5	4.4	4.4	4.4	4.4	4.3	4.3	4.3	4.2
			10.0	4.6	4.6	4.6	4.5	4.6	4.6	4.5	4.5	4.5	4.5	4.4	4.4	4.4	4.4	4.4	4.3	4.2

