

# 屋内照明器具特性

|         |                        |  |  |  |  |
|---------|------------------------|--|--|--|--|
| 品番 (品名) | LGB15398               |  |  |  |  |
| 光源      | LLD2000CU1 x1 566.0 lm |  |  |  |  |
| 管理番号    | K0178767(0)DR1         |  |  |  |  |
| BZ分類    | BZ1/1.1/BZ2            |  |  |  |  |

|        |               |         |      |    |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    |     |    |
|--------|---------------|---------|------|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|----|-----|----|
| 器具効率   | 64%           | 天井      | 80%  |    |    |     | 70% |    |    |     | 50% |    |    |     | 30% |    |    |     | 0% |     |    |
|        | 上方光束          |         | 2%   | 壁  | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30  | 10 | 70 | 50  | 30 | 10  | 0% |
|        | 下方光束          |         | 62%  |    | 床  | 10% |     |    |    | 10% |     |    |    | 10% |     |    |    | 10% |    |     |    |
| 室指数    | 照明率 ( X0.01 ) |         |      |    |    |     |     |    |    |     |     |    |    |     |     |    |    |     |    | ZCM |    |
| 保守率    | 良             | 0.67    | 0.6  | 45 | 40 | 36  | 34  | 45 | 39 | 36  | 34  | 43 | 39 | 36  | 33  | 42 | 38 | 35  | 33 | 32  |    |
|        | 中             | 0.63    | 0.8  | 51 | 45 | 42  | 40  | 50 | 45 | 42  | 39  | 48 | 44 | 41  | 39  | 47 | 43 | 41  | 39 | 38  |    |
|        | 否             | 0.56    | 1.0  | 54 | 49 | 46  | 44  | 53 | 49 | 46  | 43  | 51 | 48 | 45  | 43  | 50 | 47 | 45  | 43 | 41  |    |
|        |               |         | 1.25 | 57 | 53 | 50  | 47  | 56 | 52 | 49  | 47  | 54 | 51 | 48  | 46  | 53 | 50 | 48  | 46 | 45  |    |
| 下方投影面積 |               |         | 1.5  | 59 | 55 | 52  | 50  | 58 | 54 | 52  | 49  | 56 | 53 | 51  | 49  | 54 | 52 | 50  | 48 | 47  |    |
|        | 等価発光面積        |         | 2.0  | 61 | 58 | 56  | 53  | 60 | 57 | 55  | 53  | 58 | 56 | 54  | 52  | 57 | 55 | 53  | 52 | 50  |    |
| 取付高さ   | 器具間隔最大限       |         | 2.5  | 62 | 60 | 58  | 56  | 62 | 59 | 57  | 56  | 60 | 58 | 56  | 55  | 58 | 57 | 55  | 54 | 52  |    |
|        | 横方向 (A)       | 縦方向 (B) | 3.0  | 63 | 61 | 59  | 58  | 63 | 61 | 59  | 57  | 61 | 59 | 58  | 56  | 59 | 58 | 56  | 55 | 54  |    |
| Hm     | 1.26Hm        | 1.26Hm  | 4.0  | 65 | 63 | 61  | 60  | 64 | 62 | 61  | 60  | 62 | 61 | 60  | 58  | 60 | 59 | 58  | 57 | 56  |    |
|        |               |         | 5.0  | 65 | 64 | 63  | 62  | 65 | 63 | 62  | 61  | 63 | 62 | 61  | 60  | 61 | 60 | 59  | 59 | 57  |    |
|        |               |         | 7.0  | 66 | 65 | 64  | 63  | 65 | 64 | 64  | 63  | 64 | 63 | 62  | 61  | 62 | 61 | 61  | 60 | 58  |    |
|        |               |         | 10.0 | 67 | 66 | 66  | 65  | 66 | 65 | 65  | 64  | 64 | 64 | 63  | 63  | 63 | 62 | 62  | 61 | 59  |    |

