

屋内照明器具特性

品番 (品名)	LGB15398		
光源	LLD2020CU1 ×1	468.0 lm	
管理番号	K0179034(0)DR1		
BZ分類	BZ1		

器具効率	95%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	95%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	83	78	75	72	82	78	75	72	81	77	74	72	80	76	74	72	71	
	中 0.63	0.8	88	83	80	78	87	83	80	78	86	82	80	78	85	81	79	77	76	
	否 0.56	1.0	91	87	84	82	90	86	83	81	88	85	83	81	87	84	82	81	80	
下方投影面積	cm ²	1.25	93	90	87	85	92	89	87	85	91	88	86	84	89	87	85	84	82	
		1.5	95	92	89	87	94	91	89	87	92	90	88	86	91	89	87	86	84	
等価発光面積	cm ²	2.0	97	94	92	90	96	94	92	90	94	92	91	89	93	91	90	88	87	
		2.5	98	96	94	92	97	95	93	92	95	94	92	91	94	92	91	90	88	
取付高さ	器具間隔最大限		3.0	99	97	95	94	98	96	95	93	96	95	93	92	94	93	92	91	89
	横方向 (A)	縦方向 (B)	4.0	100	98	97	96	99	98	96	95	97	96	95	94	95	94	93	93	91
Hm	0.35Hm	0.35Hm	5.0	101	99	98	97	99	98	97	96	97	97	96	95	96	95	94	94	91
			7.0	101	100	99	99	100	99	99	98	98	97	97	96	96	96	95	95	92
			10.0	102	101	100	100	100	100	99	99	99	98	98	97	97	96	96	93	

