

屋内照明器具特性

品番 (品名)	LGB15398				
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 1m				
管理番号	K0184642 (0) DR1				
BZ分類	BZ1 / 0.9 / BZ2				

器具効率	58%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		55%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01) ZCM																				
保守率	良	0.67	0.6	41	36	32	30	40	35	32	30	39	35	32	30	38	34	31	30	29	
	中	0.63	0.8	46	41	38	36	45	41	38	35	43	40	37	35	42	39	36	35	33	
	否	0.56	1.0	49	44	41	39	48	44	41	39	46	43	40	38	45	42	40	38	37	
			1.25	51	48	45	43	50	47	44	42	49	46	43	42	47	45	43	41	40	
下方投影面積			1.5	53	50	47	45	52	49	46	45	50	48	46	44	49	46	45	43	42	
			2.0	55	52	50	48	54	52	50	48	52	50	48	47	51	49	47	46	44	
取付高さ	器具間隔最大限		2.5	57	54	52	51	56	53	52	50	54	52	50	49	52	50	49	48	46	
	横方向 (A)	縦方向 (B)	3.0	57	55	54	52	56	55	53	52	55	53	52	50	53	52	50	49	47	
Hm	1.23Hm	1.23Hm	4.0	59	57	56	54	58	56	55	54	56	55	53	52	54	53	52	51	49	
			5.0	59	58	57	56	58	57	56	55	56	55	54	54	55	54	53	52	50	
			7.0	60	59	58	57	59	58	57	57	57	56	56	55	55	55	55	54	51	
			10.0	61	60	59	59	60	59	58	58	58	57	57	56	56	56	55	55	52	

