

|          |                        |
|----------|------------------------|
| 屋内照明器具特性 |                        |
| 品番 (品名)  | LGB16702               |
| 光源       | LLD3000CU1 x1 795.0 lm |
| 管理番号     | K0179082(0)DR1         |
| BZ分類     | BZ1                    |

|        |         |               |             |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|---------|---------------|-------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 55%     | 天井            | 80%         |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |         | 壁             | 70          | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 0%      | 床             | 10%         |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 55%     | 室指数           | 照明率 (X0.01) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.67          | 0.6         | 4.2 | 3.8 | 3.6 | 3.4 | 4.2 | 3.8 | 3.5 | 3.4 | 4.1 | 3.7 | 3.5 | 3.4 | 4.0 | 3.7 | 3.5 | 3.3 | 3.3 |
|        | 中       | 0.63          | 0.8         | 4.6 | 4.3 | 4.0 | 3.9 | 4.6 | 4.3 | 4.0 | 3.8 | 4.5 | 4.2 | 4.0 | 3.8 | 4.4 | 4.1 | 4.0 | 3.8 | 3.7 |
|        | 否       | 0.56          | 1.0         | 4.9 | 4.6 | 4.3 | 4.2 | 4.8 | 4.5 | 4.3 | 4.2 | 4.7 | 4.5 | 4.3 | 4.1 | 4.6 | 4.4 | 4.3 | 4.1 | 4.0 |
|        |         |               | 1.25        | 5.1 | 4.8 | 4.6 | 4.4 | 5.0 | 4.8 | 4.6 | 4.4 | 4.9 | 4.7 | 4.5 | 4.4 | 4.8 | 4.7 | 4.5 | 4.4 | 4.3 |
| 下方投影面積 |         | $\text{cm}^2$ | 1.5         | 5.2 | 5.0 | 4.8 | 4.6 | 5.2 | 5.0 | 4.8 | 4.6 | 5.1 | 4.9 | 4.7 | 4.6 | 5.0 | 4.8 | 4.7 | 4.6 | 4.5 |
| 等価発光面積 |         | $\text{cm}^2$ | 2.0         | 5.4 | 5.2 | 5.1 | 4.9 | 5.4 | 5.2 | 5.0 | 4.9 | 5.2 | 5.1 | 5.0 | 4.8 | 5.1 | 5.0 | 4.9 | 4.8 | 4.7 |
| 取付高さ   | 器具間隔最大限 |               | 2.5         | 5.5 | 5.3 | 5.2 | 5.1 | 5.5 | 5.3 | 5.2 | 5.1 | 5.3 | 5.2 | 5.1 | 5.0 | 5.2 | 5.1 | 5.0 | 4.9 | 4.8 |
|        | 横方向 (A) | 縦方向 (B)       | 3.0         | 5.6 | 5.4 | 5.3 | 5.2 | 5.5 | 5.4 | 5.3 | 5.2 | 5.4 | 5.3 | 5.2 | 5.1 | 5.3 | 5.2 | 5.1 | 5.0 | 4.9 |
| Hm     | 0.70Hm  | 0.70Hm        | 4.0         | 5.7 | 5.6 | 5.5 | 5.4 | 5.6 | 5.5 | 5.4 | 5.3 | 5.5 | 5.4 | 5.3 | 5.3 | 5.4 | 5.3 | 5.2 | 5.2 | 5.1 |
|        |         |               | 5.0         | 5.7 | 5.6 | 5.5 | 5.5 | 5.7 | 5.6 | 5.5 | 5.4 | 5.5 | 5.5 | 5.4 | 5.3 | 5.4 | 5.4 | 5.3 | 5.3 | 5.1 |
|        |         |               | 7.0         | 5.8 | 5.7 | 5.6 | 5.6 | 5.7 | 5.6 | 5.6 | 5.5 | 5.6 | 5.5 | 5.5 | 5.4 | 5.5 | 5.4 | 5.4 | 5.4 | 5.2 |
|        |         |               | 10.0        | 5.8 | 5.8 | 5.7 | 5.7 | 5.8 | 5.7 | 5.7 | 5.6 | 5.6 | 5.6 | 5.6 | 5.5 | 5.5 | 5.5 | 5.5 | 5.4 | 5.3 |

