

# 屋内照明器具特性

品番 (品名) **LGB15393**

光源 **LLD2020LCE1 x1** **460.0 lm**

管理番号 **K0175761(0)DR1**

BZ分類 **BZ1**

器具効率	79 %	天井	80 %				70 %				50 %				30 %				0 %
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %
下方光束	79 %		室指数	照明率 ( X0.01 )															
保守率	良 0.67	0.6	71	67	65	63	70	67	65	63	69	66	64	63	69	66	64	63	62
	中 0.63	0.8	75	71	69	67	74	71	69	67	73	70	68	67	72	70	68	67	66
	否 0.56	1.0	77	74	72	70	76	74	72	70	75	73	71	70	74	72	71	69	69
下方投影面積	cm <sup>2</sup>	1.25	79	76	74	73	78	76	74	72	77	75	73	72	76	74	73	72	71
		1.5	80	78	76	74	79	77	75	74	78	76	75	74	77	75	74	73	72
等価発光面積	cm <sup>2</sup>	2.0	81	80	78	77	81	79	78	76	79	78	77	76	78	77	76	75	74
		2.5	82	81	79	78	82	80	79	78	80	79	78	77	79	78	77	76	75
取付高さ	器具間隔最大限		3.0	83	82	80	79	82	81	80	79	81	80	79	78	79	78	77	75
	横方向 (A)	縦方向 (B)	4.0	84	83	82	81	83	82	81	80	81	80	80	79	80	79	79	76
H <sub>m</sub>	0.42H <sub>m</sub>	0.42H <sub>m</sub>	5.0	84	83	82	82	83	82	82	81	82	81	80	80	80	80	79	77
			7.0	85	84	83	83	84	83	83	82	82	82	81	81	81	80	80	77
			10.0	85	85	84	84	84	84	83	83	82	82	82	81	81	81	80	78

