

屋内照明器具特性	
品番 (品名)	LGB15393
光源	LLD2000MLCE1 ×1 531.0 l m
管理番号	K0175766(0)DR1
BZ分類	BZ1

器具効率	30%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	30%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	2.8	2.7	2.6	2.5	2.8	2.7	2.6	2.5	2.7	2.6	2.6	2.5	2.7	2.6	2.6	2.5	2.5
	中	0.63	0.8	2.9	2.8	2.7	2.7	2.9	2.8	2.7	2.7	2.8	2.8	2.7	2.6	2.8	2.7	2.7	2.6	2.6
	否	0.56	1.0	3.0	2.9	2.8	2.7	2.9	2.9	2.8	2.7	2.9	2.8	2.8	2.7	2.9	2.8	2.8	2.7	2.7
			1.25	3.0	2.9	2.9	2.8	3.0	2.9	2.9	2.8	2.9	2.9	2.8	2.8	2.9	2.9	2.8	2.8	2.7
下方投影面積			1.5	3.0	3.0	2.9	2.9	3.0	3.0	2.9	2.9	3.0	2.9	2.9	2.8	2.9	2.9	2.9	2.8	2.8
			2.0	3.1	3.0	3.0	2.9	3.1	3.0	3.0	2.9	3.0	3.0	2.9	2.9	3.0	2.9	2.9	2.9	2.8
取付高さ	器具間隔最大限		2.5	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	3.0	3.0	2.9	3.0	3.0	2.9	2.9	2.9	2.9
	横方向 (A)	縦方向 (B)	3.0	3.1	3.1	3.1	3.0	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	3.0	3.0	3.0	2.9	2.9
Hm	0.75Hm	0.75Hm	4.0	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.1	3.0	3.0	3.0	3.0	3.0	3.0	3.0	2.9
			5.0	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	3.0	3.0	3.0	2.9
			7.0	3.2	3.2	3.2	3.1	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	2.9
			10.0	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	2.9

