

# 屋内照明器具特性

品番 (品名) **LGB16737**

光源 **LLD3020LCB1 x1** **795.0 lm**

管理番号 **K0176234(0)DR1**

BZ分類 **BZ1**

器具効率	60%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	60%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	0.6	50	46	44	42	50	46	44	42	49	46	44	42	48	45	43	42	41	
	中 0.63	0.8	54	50	48	46	53	50	48	46	52	49	47	46	51	49	47	46	45	
	否 0.56	1.0	56	53	50	49	55	52	50	49	54	52	50	48	53	51	49	48	47	
下方投影面積	cm <sup>2</sup>	1.25	58	55	53	51	57	54	53	51	56	54	52	51	55	53	52	50	50	
		1.5	59	56	54	53	58	56	54	53	57	55	54	52	56	54	53	52	51	
等価発光面積	cm <sup>2</sup>	2.0	60	58	57	55	60	58	56	55	59	57	56	55	57	56	55	54	53	
		2.5	61	60	58	57	61	59	58	57	59	58	57	56	58	57	56	55	54	
取付高さ	器具間隔最大限		3.0	62	61	59	58	61	60	59	58	60	59	58	57	59	58	57	56	55
	横方向 (A)	縦方向 (B)	4.0	63	62	61	60	62	61	60	59	61	60	59	58	60	59	58	58	56
Hm	0.47Hm	0.47Hm	5.0	63	62	61	61	63	62	61	60	61	61	60	59	60	59	59	58	57
			7.0	64	63	63	62	63	63	62	61	62	61	61	60	61	60	60	59	58
			10.0	64	64	63	63	64	63	63	62	62	62	62	61	61	61	60	60	58

