

屋内照明器具特性

品番 (品名) **LGB15393**

光源 **LLD3020MLCB1 ×1** 715.0 lm

管理番号 **K0175755(0)DR1**

BZ分類 **BZ1**

器具効率	69%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	69%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	

保守率	良	0.67	0.6	61	58	56	54	61	58	56	54	60	57	55	54	59	57	55	54	53
	中	0.63	0.8	64	61	59	58	64	61	59	58	63	61	59	58	62	60	59	58	57
	否	0.56	1.0	66	64	62	60	66	63	62	60	65	63	61	60	64	62	61	60	59
下方投影面積	等価発光面積	cm ²	1.25	68	66	64	63	67	65	64	62	66	65	63	62	65	64	63	62	61
			1.5	69	67	65	64	68	66	65	64	67	66	64	63	66	65	64	63	62
取付高さ	器具間隔最大限		2.0	70	69	67	66	70	68	67	66	68	67	66	65	67	66	65	65	63
	横方向 (A)	縦方向 (B)	2.5	71	70	68	67	70	69	68	67	69	68	67	66	68	67	66	66	64
H _m	0.42H _m	0.42H _m	3.0	72	70	69	68	71	70	69	68	70	69	68	67	68	68	67	66	65
			4.0	72	71	70	70	71	71	70	69	70	69	69	68	69	68	68	67	66
			5.0	73	72	71	70	72	71	70	70	70	70	69	69	69	69	68	68	66
			7.0	73	72	72	71	72	72	71	71	71	70	70	70	69	69	69	68	67
			10.0	73	73	73	72	73	72	72	71	71	71	70	70	70	69	69	69	67

