

# 屋内照明器具特性

品番 (品名) **LGB16737**

光源 **LLD2020LCB1 x1** **460.0 lm**

管理番号 **K0176235(0)DR1**

BZ分類 **BZ1**

器具効率	80%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	80%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良 0.67	0.6	67	62	59	57	66	62	59	56	65	61	58	56	64	61	58	56	55	
	中 0.63	0.8	71	67	64	62	71	67	64	62	70	66	63	61	68	65	63	61	60	
	否 0.56	1.0	74	70	67	65	74	70	67	65	72	69	67	65	71	68	66	64	63	
下方投影面積 等価発光面積	c m <sup>2</sup>	1.25	77	73	70	68	76	73	70	68	75	72	69	68	73	71	69	67	66	
		1.5	78	75	73	71	78	75	72	70	76	74	72	70	75	73	71	69	68	
		2.0	81	78	76	74	80	77	75	74	78	76	74	73	77	75	73	72	71	
取付 高さ	器具間隔最大限		2.5	82	80	78	76	81	79	77	76	79	78	76	75	78	76	75	74	72
	横方向 (A)	縦方向 (B)	3.0	83	81	79	78	82	80	78	77	80	79	77	76	79	77	76	75	74
H <sub>m</sub>	0.47H <sub>m</sub>	0.47H <sub>m</sub>	4.0	84	82	81	80	83	81	80	79	81	80	79	78	80	79	78	77	75
			5.0	84	83	82	81	84	82	81	80	82	81	80	79	80	79	79	78	76
			7.0	85	84	83	83	84	83	83	82	83	82	81	81	81	80	80	79	77
			10.0	86	85	84	84	85	84	84	83	83	83	82	82	81	81	81	80	78

