

# 屋内照明器具特性

品番 (品名)	LGB16703														
光源	LLD2000MLCE1 ×1 531.0 lm														
管理番号	K0175766(0)DR1														
BZ分類	BZ1														

器具効率	30%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	0% 30%	室指数	照明率 (X0.01) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	2.8	2.7	2.6	2.5	2.8	2.7	2.6	2.5	2.7	2.6	2.6	2.5	2.7	2.6	2.6	2.5	2.5		
		0.8	2.9	2.8	2.7	2.7	2.9	2.8	2.7	2.7	2.8	2.8	2.7	2.6	2.8	2.7	2.7	2.6	2.6		
		1.0	3.0	2.9	2.8	2.7	2.9	2.9	2.8	2.7	2.9	2.8	2.8	2.7	2.9	2.8	2.8	2.7	2.7		
		1.25	3.0	2.9	2.9	2.8	3.0	2.9	2.9	2.8	2.9	2.9	2.8	2.8	2.9	2.9	2.8	2.8	2.7		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	3.0	3.0	2.9	2.9	3.0	3.0	2.9	2.9	3.0	2.9	2.9	2.8	2.9	2.9	2.9	2.8	2.8		
		2.0	3.1	3.0	3.0	2.9	3.1	3.0	3.0	2.9	3.0	3.0	2.9	2.9	3.0	2.9	2.9	2.9	2.8		
取付高さ H m	器具間隔最大限		2.5	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	3.0	3.0	2.9	3.0	3.0	2.9	2.9	2.9		
	横方向 (A) 0.75 H m	縦方向 (B) 0.75 H m	3.0	3.1	3.1	3.1	3.0	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	3.0	3.0	2.9	2.9		
			4.0	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.1	3.0	3.0	3.0	3.0	3.0	3.0	2.9		
			5.0	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	3.0	3.0	3.0	2.9		
			7.0	3.2	3.2	3.2	3.1	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	2.9		
			10.0	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	3.0	2.9		

