

屋内照明器具特性	
品番 (品名)	LGB16703
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0175654(0)DR1
BZ分類	BZ1

器具効率	31%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	31%																			
保守率	良 中 否 0.67 0.63 0.56	0.6	2.9	2.8	2.7	2.7	2.9	2.8	2.7	2.7	2.9	2.8	2.7	2.7	2.8	2.8	2.7	2.7	2.6	
		0.8	3.0	2.9	2.8	2.8	3.0	2.9	2.8	2.8	3.0	2.9	2.8	2.8	2.9	2.9	2.8	2.8	2.7	
		1.0	3.1	3.0	2.9	2.9	3.1	3.0	2.9	2.9	3.0	2.9	2.9	2.8	3.0	2.9	2.9	2.8	2.8	
		1.25	3.1	3.0	3.0	2.9	3.1	3.0	3.0	2.9	3.1	3.0	3.0	2.9	3.0	3.0	2.9	2.9	2.9	
下方投影面積	c m ²	1.5	3.2	3.1	3.0	3.0	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	3.0	3.0	3.0	2.9	2.9	
		2.0	3.2	3.1	3.1	3.1	3.2	3.1	3.1	3.0	3.1	3.1	3.0	3.0	3.1	3.0	3.0	3.0	2.9	
取付高さ	器具間隔最大限		2.5	3.2	3.2	3.1	3.1	3.2	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.0	3.0	
	横方向 (A)	縦方向 (B)	3.0	3.2	3.2	3.2	3.1	3.2	3.2	3.1	3.1	3.2	3.1	3.1	3.1	3.1	3.1	3.1	3.0	
H m	0.77H m	0.77H m	4.0	3.3	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.1	3.1	3.1		
			5.0	3.3	3.3	3.2	3.2	3.3	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.1	3.0	
			7.0	3.3	3.3	3.3	3.2	3.3	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.0	
			10.0	3.3	3.3	3.3	3.3	3.3	3.3	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.1	3.1	3.0	

