

# 屋内照明器具特性

品番 (品名) **LGB16703**

光源 **LLD3020CU1 ×1** **615.0 1m**

管理番号 **K0179091(0)DR1**

BZ分類 **BZ1**

器具効率	72%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	72%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X 0.01 )																ZCM	
保守率	良 0.67	0.6	66	63	61	59	65	62	60	59	65	62	60	59	64	62	60	59	58	
	中 0.63	0.8	69	66	64	63	68	66	64	63	68	65	64	62	67	65	63	62	62	
	否 0.56	1.0	71	68	66	65	70	68	66	65	69	67	66	65	68	67	65	64	64	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	72	70	68	67	72	70	68	67	71	69	68	66	70	68	67	66	65	
		1.5	73	71	70	68	73	71	69	68	71	70	69	68	70	69	68	67	66	
		2.0	74	73	72	70	74	72	71	70	73	71	70	69	71	70	70	69	68	
取付高さ	器具間隔最大限		2.5	75	74	73	72	75	73	72	71	73	72	71	71	72	71	70	68	
	横方向 (A)	縦方向 (B)	3.0	76	75	73	73	75	74	73	72	74	73	72	71	72	72	71	69	
Hm	0.35Hm	0.35Hm	4.0	76	75	75	74	76	75	74	73	74	74	73	72	73	72	71	70	
			5.0	77	76	75	75	76	75	75	74	75	74	73	73	73	73	72	70	
			7.0	77	77	76	76	76	76	75	75	75	74	74	74	73	73	73	71	
			10.0	77	77	77	76	77	76	76	76	75	75	75	74	74	73	73	71	

