

屋内照明器具特性

| | | |
|---------|------------------|----------|
| 品番 (品名) | LGB15397 | |
| 光源 | LLD2020LCB1 ×1 | 460.0 lm |
| 管理番号 | K0175675 (1) DR1 | |
| BZ分類 | BZ1 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------------|-----------------|------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|-----|
| 器具効率 | 87% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 | | 0% | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 87% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.67 | 0.6 | 74 | 69 | 66 | 64 | 73 | 69 | 66 | 64 | 72 | 68 | 66 | 64 | 71 | 68 | 65 | 63 | 63 |
| | 中 | 0.63 | 0.8 | 79 | 74 | 71 | 69 | 78 | 74 | 71 | 69 | 77 | 73 | 71 | 69 | 76 | 73 | 70 | 69 | 68 |
| | 否 | 0.56 | 1.0 | 82 | 78 | 75 | 73 | 81 | 77 | 75 | 73 | 80 | 77 | 74 | 72 | 78 | 76 | 74 | 72 | 71 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 84 | 81 | 78 | 76 | 84 | 80 | 78 | 76 | 82 | 79 | 77 | 76 | 81 | 78 | 77 | 75 | 74 |
| | | | 1.5 | 86 | 83 | 80 | 79 | 85 | 82 | 80 | 78 | 84 | 81 | 79 | 78 | 82 | 80 | 78 | 77 | 76 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 88 | 86 | 83 | 82 | 87 | 85 | 83 | 81 | 86 | 84 | 82 | 81 | 84 | 82 | 81 | 80 | 78 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 89 | 87 | 85 | 84 | 88 | 86 | 85 | 83 | 87 | 85 | 84 | 82 | 85 | 84 | 83 | 82 | 80 |
| Hm | 0.41Hm | 0.41Hm | 3.0 | 90 | 88 | 87 | 85 | 89 | 87 | 86 | 85 | 87 | 86 | 85 | 84 | 86 | 85 | 84 | 83 | 81 |
| | | | 4.0 | 91 | 90 | 88 | 87 | 90 | 89 | 88 | 87 | 88 | 87 | 86 | 85 | 87 | 86 | 85 | 84 | 82 |
| | | | 5.0 | 92 | 91 | 89 | 88 | 91 | 90 | 89 | 88 | 89 | 88 | 87 | 86 | 87 | 86 | 86 | 85 | 83 |
| | | | 7.0 | 92 | 92 | 91 | 90 | 91 | 91 | 90 | 89 | 90 | 89 | 88 | 88 | 88 | 87 | 87 | 86 | 84 |
| | | | 10.0 | 93 | 92 | 92 | 91 | 92 | 91 | 91 | 90 | 90 | 90 | 89 | 89 | 88 | 88 | 87 | 87 | 85 |

