

屋内照明器具特性

品番 (品名)	NNCF43235J (J Y O U J I _ C E I L I N)									
光源	LED5000_85_3800 ×1 3800.0 lm									
管理番号	K0194810 (3) DR 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	6 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	94 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.83	0.6	5.5	4.3	3.5	3.0	5.3	4.2	3.5	2.9	5.0	4.0	3.4	2.9	4.8	3.9	3.3	2.8	2.6
	中	0.81	0.8	6.5	5.3	4.5	4.0	6.3	5.2	4.5	3.9	6.0	5.0	4.4	3.9	5.7	4.8	4.3	3.8	3.5
	否	0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.7	6.6	5.7	5.1	4.6	6.2	5.5	4.9	4.5	4.2
			1.25	7.8	6.8	6.0	5.5	7.6	6.6	6.0	5.4	7.2	6.4	5.8	5.3	6.8	6.1	5.6	5.2	4.9
下方投影面積			1.5	8.2	7.3	6.6	6.0	8.0	7.1	6.5	6.0	7.6	6.9	6.3	5.8	7.2	6.6	6.1	5.7	5.4
等価発光面積			2.0	8.7	8.0	7.4	6.9	8.5	7.8	7.3	6.8	8.1	7.5	7.0	6.6	7.7	7.2	6.8	6.5	6.1
取付高さ	器具間隔最大限		2.5	9.1	8.5	7.9	7.4	8.9	8.3	7.8	7.4	8.5	8.0	7.5	7.2	8.1	7.7	7.3	7.0	6.6
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.9	9.1	8.6	8.2	7.8	8.7	8.3	7.9	7.6	8.3	8.0	7.7	7.4	7.0
1.5m	2.01m	2.13m	4.0	9.7	9.2	8.8	8.5	9.5	9.0	8.7	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.5
2	2.66	2.72	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	8.9	8.6	8.4	8.2	7.8
2.5	3.31	3.32	7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.2	9.5	9.3	9.1	8.9	9.1	8.9	8.8	8.6	8.2
3	3.96	3.94	10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.7	9.5	9.7	9.5	9.4	9.2	9.3	9.2	9.1	8.9	8.5

