

屋内照明器具特性

品番 (品名) **LGB15397**

光源 **LLD40402CQ1 (SHUKOU) ×1** 620.0 1 m

管理番号 **K0184643 (0) DR 1**

BZ分類 **BZ1**

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 1 %		70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	84 %	床	10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X0.01)	ZCM																	
保守率	良 0.67	0.6	75	71	69	67	75	71	69	67	74	70	68	67	73	70	68	66	66	
	中 0.63	0.8	79	75	73	71	78	75	73	71	77	74	72	71	76	74	72	70	69	
	否 0.56	1.0	81	78	76	74	81	78	75	74	79	77	75	73	78	76	74	73	72	
下方投影面積 等価発光面積	c m ²	1.25	83	80	78	76	83	80	78	76	81	79	77	76	80	78	76	75	74	
		1.5	85	82	80	78	84	81	79	78	82	80	79	77	81	79	78	77	75	
取付高さ	器具間隔最大限		2.5	87	85	84	82	86	85	83	82	85	83	82	81	83	82	81	80	78
	横方向 (A)	縦方向 (B)	3.0	88	86	85	84	87	86	84	83	85	84	83	82	83	83	82	81	79
H m	0.78 H m	0.78 H m	4.0	89	87	86	85	88	87	86	85	86	85	84	83	84	83	83	82	80
			5.0	89	88	87	86	88	87	86	86	86	86	85	84	85	84	83	83	81
			7.0	90	89	88	88	89	88	88	87	87	86	86	85	85	85	84	84	81
			10.0	90	90	89	89	89	88	88	87	87	87	86	85	85	85	84	82	

