

屋内照明器具特性

品番 (品名)	LGB16707														
光源	LLD3000CU1 x1 795.0 lm														
管理番号	K0178766(0)DR1														
BZ分類	BZ1/1.1/BZ2														

器具効率	60%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	1%	室指数	照明率 (X0.01)																ZCM		
下方光束	59%																				
保守率	良 中 否	0.67	0.6	43	38	34	32	42	37	34	32	41	37	34	32	40	36	33	32	31	
		0.63	0.8	48	43	40	37	47	43	40	37	46	42	39	37	45	41	39	37	36	
		0.56	1.0	51	47	44	41	50	46	43	41	49	45	43	41	47	45	42	40	39	
			1.25	54	50	47	45	53	49	47	45	51	48	46	44	50	47	45	44	42	
下方投影面積	c m ²	1.5	56	52	49	47	55	51	49	47	53	50	48	46	52	49	47	46	45		
		2.0	58	55	53	51	57	54	52	50	55	53	51	50	54	52	50	49	48		
取付高さ	器具間隔最大限		2.5	59	57	55	53	58	56	54	53	57	55	53	52	55	54	52	51	50	
	横方向 (A)	縦方向 (B)	3.0	60	58	56	55	59	57	56	54	58	56	55	53	56	55	54	53	51	
H m	1.26 H m	1.26 H m	4.0	61	60	58	57	61	59	58	57	59	58	56	55	57	56	55	54	53	
			5.0	62	61	60	58	61	60	59	58	60	59	58	57	58	57	56	56	54	54
			7.0	63	62	61	60	62	61	60	60	60	60	59	58	59	58	58	57	55	
			10.0	64	63	62	62	63	62	61	61	61	60	60	59	59	59	59	58	56	

