

屋内照明器具特性

| | | | |
|---------|--|--|--|
| 品番 (品名) | LGB16707 | | |
| 光源 | LLD40402CQ1 (SHUKOU) ×1 620.0 1 m | | |
| 管理番号 | K0184643 (0) DR 1 | | |
| BZ分類 | BZ1 | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|-----|
| 器具効率 | 85 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
| | 上方光束 | | 1 % | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % |
| 下方光束 | 84 % | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 室指数 | | 照明率 (X0.01) | ZCM | | | | | | | | | | | | | | | | | |
| 保守率 | 良 | 0.67 | 0.6 | 75 | 71 | 69 | 67 | 75 | 71 | 69 | 67 | 74 | 70 | 68 | 67 | 73 | 70 | 68 | 66 | 66 |
| | 中 | 0.63 | 0.8 | 79 | 75 | 73 | 71 | 78 | 75 | 73 | 71 | 77 | 74 | 72 | 71 | 76 | 74 | 72 | 70 | 69 |
| | 否 | 0.56 | 1.0 | 81 | 78 | 76 | 74 | 81 | 78 | 75 | 74 | 79 | 77 | 75 | 73 | 78 | 76 | 74 | 73 | 72 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 83 | 80 | 78 | 76 | 83 | 80 | 78 | 76 | 81 | 79 | 77 | 76 | 80 | 78 | 76 | 75 | 74 |
| | | | 1.5 | 85 | 82 | 80 | 78 | 84 | 81 | 79 | 78 | 82 | 80 | 79 | 77 | 81 | 79 | 78 | 77 | 75 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 86 | 84 | 82 | 81 | 85 | 83 | 82 | 80 | 84 | 82 | 81 | 79 | 82 | 81 | 80 | 79 | 77 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 87 | 85 | 84 | 82 | 86 | 85 | 83 | 82 | 85 | 83 | 82 | 81 | 83 | 82 | 81 | 80 | 78 |
| Hm | 0.78Hm | 0.78Hm | 3.0 | 88 | 86 | 85 | 84 | 87 | 86 | 84 | 83 | 85 | 84 | 83 | 82 | 83 | 83 | 82 | 81 | 79 |
| | | | 4.0 | 89 | 87 | 86 | 85 | 88 | 87 | 86 | 85 | 86 | 85 | 84 | 83 | 84 | 83 | 83 | 82 | 80 |
| | | | 5.0 | 89 | 88 | 87 | 86 | 88 | 87 | 86 | 86 | 86 | 86 | 85 | 84 | 85 | 84 | 83 | 81 | |
| | | | 7.0 | 90 | 89 | 88 | 88 | 89 | 88 | 88 | 87 | 87 | 86 | 86 | 85 | 85 | 85 | 84 | 81 | |
| | | | 10.0 | 90 | 90 | 89 | 89 | 89 | 88 | 88 | 87 | 87 | 87 | 86 | 85 | 85 | 85 | 84 | 82 | |

