

屋内照明器具特性	
品番 (品名)	LGB15398
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0175770 (0) DR 1
BZ分類	BZ1 / 1.1 / BZ2

器具効率	63 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	2 %	室指数	照明率 (X0.01)																ZCM	
下方光束	61 %																			
保守率	良 中 否 0.67 0.63 0.56	0.6	45	39	36	33	44	39	35	33	43	38	35	33	42	38	35	33	32	
		0.8	50	45	41	39	49	44	41	39	48	44	41	39	46	43	40	38	37	
		1.0	53	49	45	43	52	48	45	43	51	47	44	42	49	46	44	42	41	
		1.25	56	52	49	47	55	51	49	46	53	50	48	46	52	49	47	45	44	
下方投影面積	c m ²	1.5	58	54	51	49	57	54	51	49	55	52	50	48	54	51	49	48	46	
		2.0	60	57	55	53	59	56	54	52	57	55	53	52	56	54	52	51	49	
取付高さ	器具間隔最大限		2.5	62	59	57	55	61	58	56	55	59	57	55	54	57	56	54	51	
	横方向 (A)	縦方向 (B)	3.0	63	60	59	57	62	60	58	56	60	58	57	56	58	57	56	53	
H m	1.26 H m	1.26 H m	4.0	64	62	61	59	63	61	60	59	61	60	59	58	59	58	57	55	
			5.0	65	63	62	61	64	62	61	60	62	61	60	59	60	59	59	56	
			7.0	65	64	63	63	64	64	63	62	63	62	61	61	61	60	60	57	
			10.0	66	65	65	64	65	64	64	63	63	63	62	62	62	61	61	58	

