

# 屋内照明器具特性

品番 (品名) **LGB15398**

光源 **LLD2020LCB1 x1**      **460.0 l m**

管理番号 **K0175675 (1) DR 1**

BZ分類 **BZ1**

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	87 %	床		10 %				10 %				10 %				10 %				0 %
室指数			照明率 ( X0.01 )																ZCM	
保守率	良 0.67	0.6	74	69	66	64	73	69	66	64	72	68	66	64	71	68	65	63	63	
	中 0.63	0.8	79	74	71	69	78	74	71	69	77	73	71	69	76	73	70	69	68	
	否 0.56	1.0	82	78	75	73	81	77	75	73	80	77	74	72	78	76	74	72	71	
下方投影面積	c m <sup>2</sup>	1.25	84	81	78	76	84	80	78	76	82	79	77	76	81	78	77	75	74	
		1.5	86	83	80	79	85	82	80	78	84	81	79	78	82	80	78	77	76	
等価発光面積	c m <sup>2</sup>	2.0	88	86	83	82	87	85	83	81	86	84	82	81	84	82	81	80	78	
		2.5	89	87	85	84	88	86	85	83	87	85	84	82	85	84	83	82	80	
取付高さ	器具間隔最大限		3.0	90	88	87	85	89	87	86	85	87	86	85	84	86	85	84	83	81
	横方向 (A)	縦方向 (B)	4.0	91	90	88	87	90	89	88	87	88	87	86	85	87	86	85	84	82
H m	0.41 H m	0.41 H m	5.0	92	91	89	88	91	90	89	88	89	88	87	86	87	86	86	85	83
			7.0	92	92	91	90	91	91	90	89	90	89	88	88	88	87	87	86	84
			10.0	93	92	92	91	92	91	91	90	90	90	89	89	88	88	87	87	85

