

屋内照明器具特性	
品番 (品名)	LGB15398
光源	LLD2020MLCB1 ×1 460.0 1m
管理番号	K0175754 (1) DR1
BZ分類	BZ1

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	反射率	壁	80 %				70 %				50 %				30 %				0 %
下方光束	89 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	76	71	67	65	75	70	67	65	74	70	67	65	73	69	67	65	64
	中	0.63	0.8	81	76	73	71	80	76	73	71	79	75	73	71	78	74	72	70	69
	否	0.56	1.0	84	80	77	75	83	79	77	74	82	78	76	74	80	78	76	74	73
下方投影面積	c m ²	1.25	86	83	80	78	86	82	80	78	84	81	79	77	83	80	78	77	76	
		1.5	88	85	82	80	87	84	82	80	86	83	81	80	84	82	80	79	78	
等価発光面積	c m ²	2.0	90	88	86	84	89	87	85	83	88	86	84	83	86	84	83	82	80	
		2.5	92	89	87	86	91	89	87	85	89	87	86	84	87	86	85	84	82	
取付高さ	器具間隔最大限		3.0	92	90	89	87	91	90	88	87	90	88	87	86	88	87	86	85	83
H m	横方向 (A)	縦方向 (B)	4.0	93	92	91	89	92	91	90	89	91	89	88	88	89	88	87	86	84
	0.48 H m	0.48 H m	5.0	94	93	92	91	93	92	91	90	91	90	89	89	89	89	88	87	85
			7.0	95	94	93	92	94	93	92	91	92	91	91	90	90	89	89	88	86
			10.0	95	95	94	93	94	94	93	93	92	92	91	91	90	90	90	89	87

