

屋内照明器具特性

品番 (品名) **LGB16778**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0175753(1)DR1**

BZ分類 **BZ1**

器具効率	88%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	88%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	75	70	66	64	74	69	66	64	73	69	66	64	72	68	66	64	63	
	中 0.63	0.8	80	75	72	70	79	75	72	70	78	74	72	70	77	73	71	69	68	
	否 0.56	1.0	83	79	76	74	82	78	76	73	81	77	75	73	79	77	75	73	72	
下方投影面積	cm ²	1.25	85	82	79	77	85	81	79	77	83	80	78	76	82	79	77	76	75	
		1.5	87	84	81	79	86	83	81	79	85	82	80	79	83	81	79	78	77	
等価発光面積	cm ²	2.0	89	87	84	83	88	86	84	82	87	85	83	82	85	83	82	81	79	
		2.5	90	88	86	85	89	87	86	84	88	86	85	83	86	85	84	83	81	
取付高さ	器具間隔最大限		3.0	91	89	88	86	90	89	87	86	88	87	86	85	87	86	85	84	82
	横方向 (A)	縦方向 (B)	4.0	92	91	89	88	91	90	89	88	89	88	87	86	88	87	86	85	83
Hm	0.47Hm	0.47Hm	5.0	93	92	91	90	92	91	90	89	90	89	88	88	88	87	86	84	
			7.0	94	93	92	91	93	92	91	90	91	90	89	89	89	88	88	87	85
			10.0	94	93	93	92	93	93	92	91	91	91	90	90	89	89	89	88	86

