

屋内照明器具特性

品番 (品名)	LGB16778				
光源	LLD2000LCB1 ×1 531.0 l m				
管理番号	K0175673 (1) DR 1				
B Z 分類	B Z 2				

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %
上方光束	2 %	室指数	照明率 (X0.01)																		ZCM
下方光束	62 %																				
保守率	良 中 否	0.67	0.6	4.4	3.9	3.5	3.2	4.4	3.8	3.5	3.2	4.2	3.8	3.4	3.2	4.1	3.7	3.4	3.2	3.1	
		0.63	0.8	5.0	4.5	4.1	3.8	4.9	4.4	4.1	3.8	4.7	4.3	4.0	3.8	4.6	4.2	4.0	3.8	3.6	
			1.0	5.3	4.8	4.5	4.2	5.2	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.9	4.6	4.3	4.1	4.0	
		0.56	1.25	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.6	5.4	5.0	4.8	4.5	5.2	4.9	4.7	4.5	4.3	
下方投影面積	c m ²	1.5	5.8	5.4	5.1	4.9	5.7	5.4	5.1	4.9	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.7	4.6		
		2.0	6.1	5.8	5.5	5.3	6.0	5.7	5.4	5.2	5.8	5.5	5.3	5.2	5.6	5.4	5.2	5.1	4.9		
取付高さ	器具間隔最大限		2.5	6.2	6.0	5.7	5.5	6.1	5.9	5.7	5.5	5.9	5.7	5.6	5.4	5.8	5.6	5.4	5.3	5.1	
	横方向 (A)	縦方向 (B)	3.0	6.3	6.1	5.9	5.7	6.2	6.0	5.8	5.7	6.0	5.9	5.7	5.6	5.9	5.7	5.6	5.5	5.3	
H m	1.24 H m	1.24 H m	4.0	6.5	6.3	6.1	6.0	6.4	6.2	6.1	5.9	6.2	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.5	
			5.0	6.6	6.4	6.3	6.1	6.5	6.3	6.2	6.1	6.3	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6	
			7.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.3	6.4	6.3	6.2	6.1	6.2	6.1	6.0	6.0	5.8	
			10.0	6.7	6.6	6.6	6.5	6.6	6.5	6.5	6.4	6.4	6.4	6.3	6.3	6.2	6.2	6.1	6.1	5.9	

