

屋内照明器具特性

品番 (品名) **LGB16778**

光源 **LLD2020MLCE1 ×1** **460.0 lm**

管理番号 **K0175753 (1) DR1**

BZ分類 **BZ1**

器具効率	88%	天井	80%				70%				50%				30%				0%
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
下方光束	88%	床	10%				10%				10%				10%				0%
室指数			照明率 (X0.01)																ZCM

保守率	良	0.67	0.6	75	70	66	64	74	69	66	64	73	69	66	64	72	68	66	64	63
	中	0.63	0.8	80	75	72	70	79	75	72	70	78	74	72	70	77	73	71	69	68
	否	0.56	1.0	83	79	76	74	82	78	76	73	81	77	75	73	79	77	75	73	72
下方投影面積	等価発光面積	cm ²	1.25	85	82	79	77	85	81	79	77	83	80	78	76	82	79	77	76	75
			1.5	87	84	81	79	86	83	81	79	85	82	80	79	83	81	79	78	77
取付高さ	器具間隔最大限		2.5	90	88	86	85	89	87	86	84	88	86	85	83	86	85	84	83	81
	横方向 (A)	縦方向 (B)	3.0	91	89	88	86	90	89	87	86	88	87	86	85	87	86	85	84	82
H _m	0.47H _m	0.47H _m	4.0	92	91	89	88	91	90	89	88	89	88	87	86	88	87	86	85	83
			5.0	93	92	91	90	92	91	90	89	90	89	88	88	88	88	87	86	84
			7.0	94	93	92	91	93	92	91	90	91	90	89	89	89	88	88	87	85
			10.0	94	93	93	92	93	93	92	91	91	91	90	90	89	89	89	88	86

