

屋内照明器具特性	
品番 (品名)	LGB16778
光源	LLD4000MLCE1 ×1          845.0 l m
管理番号	K0175676 (1) DR 1
BZ分類	BZ2

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																							
		床	10 %				10 %				10 %				10 %				0 %																																							
上方光束	2 %	室指数																			照明率 ( X0.01 )																			ZCM																		
下方光束	60 %																																																									
保守率	良 中 否	0.67	0.6	43	37	34	31	42	37	33	31	41	36	33	31	40	36	33	31	30																																						
		0.63	0.8	48	43	39	37	47	42	39	37	46	42	39	36	44	41	38	36	35																																						
		0.56	1.0	51	47	43	41	50	46	43	41	49	45	42	40	47	44	42	40	39																																						
			1.25	54	50	47	44	53	49	46	44	52	48	46	44	50	47	45	43	42																																						
下方投影面積	c m <sup>2</sup>	1.5	56	52	49	47	55	52	49	47	53	50	48	46	52	49	47	46	44																																							
		2.0	58	55	53	51	57	55	52	50	56	53	51	50	54	52	50	49	47																																							
取付高さ	器具間隔最大限		2.5	60	57	55	53	59	57	55	53	57	55	54	52	56	54	52	51	50																																						
	横方向 (A)	縦方向 (B)	3.0	61	59	57	55	60	58	56	55	58	57	55	54	57	55	54	53	51																																						
H m	1.23 H m	1.23 H m	4.0	62	60	59	58	61	60	58	57	60	58	57	56	58	57	56	55	53																																						
			5.0	63	62	60	59	62	61	60	58	60	59	58	57	59	58	57	56	54																																						
			7.0	64	63	62	61	63	62	61	60	61	60	60	59	60	59	58	56																																							
			10.0	65	64	63	62	64	63	62	62	62	61	61	60	60	59	59	57																																							

