

屋内照明器具特性

品番 (品名) **LGB16778**

光源 **LLD3020MLCE1 x1** **795.0 lm**

管理番号 **K0175749 (1) DR1**

BZ分類 **BZ1**

器具効率	90%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	90%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.67	0.6	76	71	68	66	76	71	68	66	75	70	68	65	74	70	67	65	64	
	中 0.63	0.8	81	77	74	71	81	76	73	71	79	76	73	71	78	75	73	71	70	
	否 0.56	1.0	85	80	77	75	84	80	77	75	82	79	77	75	81	78	76	74	73	
下方投影面積	cm ²	1.25	87	83	81	79	86	83	80	78	85	82	80	78	83	81	79	77	76	
		1.5	89	86	83	81	88	85	83	81	86	84	82	80	85	83	81	79	78	
等価発光面積	cm ²	2.0	91	88	86	84	90	88	86	84	88	86	85	83	87	85	84	82	81	
		2.5	92	90	88	86	91	89	87	86	90	88	86	85	88	86	85	84	82	
取付高さ	器具間隔最大限		3.0	93	91	89	88	92	90	89	87	90	89	88	86	89	87	86	85	84
	横方向 (A)	縦方向 (B)	4.0	94	93	91	90	93	92	91	89	91	90	89	88	90	89	88	87	85
Hm	0.44Hm	0.44Hm	5.0	95	94	92	91	94	93	92	91	92	91	90	89	90	89	89	88	86
			7.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	87
			10.0	96	95	95	94	95	94	94	93	93	93	92	92	91	91	90	90	88

