

# 屋内照明器具特性

品番 (品名) **LGB16778**

光源 **LLD3020CU1 ×1**      **615.0 l m**

管理番号 **K0179033 (0) DR1**

BZ分類 **BZ1**

器具効率	91%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	91%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良 0.67	0.6	79	75	72	69	79	74	71	69	78	74	71	69	77	73	71	69	68	
	中 0.63	0.8	84	80	77	75	83	79	77	75	82	79	76	74	81	78	76	74	73	
	否 0.56	1.0	87	83	80	78	86	83	80	78	85	82	79	78	83	81	79	77	76	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	89	86	83	81	88	85	83	81	87	84	82	81	86	83	82	80	79	
		1.5	91	88	85	83	90	87	85	83	88	86	84	83	87	85	83	82	81	
		2.0	93	90	88	87	92	90	88	86	90	88	87	85	89	87	86	85	83	
取付高さ	器具間隔最大限		2.5	94	92	90	89	93	91	89	88	91	90	88	87	90	88	87	86	84
	横方向 (A)	縦方向 (B)	3.0	95	93	91	90	94	92	91	89	92	91	89	88	90	89	88	87	85
Hm	0.35Hm	0.35Hm	4.0	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	89	87
			5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	90	87
			7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	91	88
			10.0	97	97	96	96	96	96	95	95	94	94	93	93	92	92	92	91	89

