

# 屋内照明器具特性

品番 (品名)	LGB16132														
光源	LLD3000CU1 x1 795.0 lm														
管理番号	K0179093(0)DR1														
BZ分類	BZ4														

器具効率	96%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束 下方光束	9% 87%	室指数	照明率 ( X0.01 ) ZCM																		
保守率	良 中 否 0.67 0.63 0.56	0.6	55	44	37	32	54	43	37	32	51	42	36	31	48	40	35	31	28		
		0.8	65	55	48	43	63	54	47	42	60	52	46	41	57	50	45	41	38		
		1.0	71	62	55	50	69	61	55	50	66	58	53	49	62	56	51	48	45		
		1.25	77	69	62	57	75	67	61	57	71	65	60	55	67	62	58	54	51		
下方投影面積 等価発光面積	c m <sup>2</sup> c m <sup>2</sup>	1.5	81	73	67	63	79	72	66	62	75	69	64	60	71	66	62	59	55		
		2.0	86	79	74	70	84	78	73	69	79	75	71	67	76	72	68	65	62		
取付 高さ	器具間隔最大限		2.5	89	83	79	75	87	82	78	74	82	78	75	72	79	75	72	70	66	
	横方向 (A) H m	縦方向 (B) H m	3.0	91	86	82	79	89	84	81	77	84	81	78	75	81	78	75	73	69	
			4.0	93	90	86	83	91	88	85	82	87	84	82	79	83	81	79	77	73	
			5.0	95	92	89	87	93	90	87	85	89	86	84	82	85	83	81	79	75	
			7.0	97	94	92	90	95	93	91	89	91	89	87	86	87	85	84	83	78	
			10.0	98	96	95	93	96	95	93	92	92	91	89	88	88	87	86	85	80	

