

屋内照明器具特性	
品番 (品名)	P M L E L 0 2 4 2 7 N C
光源	L E D 2 7 0 0 _ 7 0 _ 5 7 0 × 1 5 7 0 . 0 l m
管理番号	K 0 1 7 7 1 9 8 (0) D Y 1
B Z 分類	B Z 2 / 1 . 1 / B Z 3 / 6 . 0 / B Z 4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		9 5 %																				
保守率		良 中 否	0 . 6 9	0 . 6	6 6	5 7	5 0	4 6	6 5	5 6	5 0	4 6	6 3	5 5	4 9	4 5	6 0	5 3	4 8	4 5	4 3	
			0 . 6 7	0 . 8	7 5	6 6	6 0	5 5	7 3	6 5	5 9	5 5	7 1	6 3	5 8	5 4	6 8	6 2	5 7	5 4	5 1	
			0 . 6 3	1 . 0	8 0	7 2	6 6	6 1	7 9	7 1	6 5	6 1	7 6	6 9	6 4	6 0	7 3	6 7	6 3	5 9	5 7	
				1 . 2 5	8 5	7 8	7 2	6 7	8 3	7 6	7 1	6 7	8 0	7 4	7 0	6 6	7 7	7 2	6 8	6 5	6 2	
下方投影面積		c m ²	1 . 5	8 8	8 1	7 6	7 2	8 7	8 0	7 5	7 1	8 3	7 8	7 4	7 0	8 0	7 6	7 2	6 9	6 6		
			2 . 0	9 3	8 7	8 2	7 8	9 1	8 6	8 1	7 8	8 7	8 3	7 9	7 6	8 4	8 1	7 7	7 5	7 2		
取付高さ	器具間隔最大限		2 . 5	9 5	9 0	8 6	8 3	9 3	8 9	8 5	8 2	9 0	8 6	8 3	8 0	8 7	8 4	8 1	7 8	7 5		
	横方向 (A) 縦方向 (B)		3 . 0	9 7	9 3	8 9	8 6	9 5	9 1	8 8	8 5	9 2	8 9	8 6	8 3	8 9	8 6	8 3	8 1	7 8		
H m	0 . 6 4 H m	1 . 1 3 H m	4 . 0	9 9	9 6	9 3	9 0	9 8	9 4	9 2	8 9	9 4	9 2	8 9	8 7	9 1	8 9	8 7	8 5	8 1		
			5 . 0	1 0 1	9 8	9 5	9 3	9 9	9 6	9 4	9 2	9 6	9 3	9 1	9 0	9 2	9 1	8 9	8 7	8 4		
			7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 7	9 6	9 4	9 3	9 4	9 3	9 2	9 0	8 6		
			1 0 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 2	1 0 1	9 9	9 8	9 9	9 8	9 6	9 5	9 6	9 5	9 4	9 3	8 9		

