

屋内照明器具特性

品番 (品名) **LGB10833**

光源 **LLD3020CU1 ×1** **615.0 lm**

管理番号 **K0179079 (0) DR1**

BZ分類 **BZ1**

| 器具効率 | 85 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | |
|--------|---------|-----------------|--------------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|----|
| | | | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | | |
| 上方光束 | 0 % | 反射率 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 下方光束 | 85 % | | 壁 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | |
| | | 床 | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | | |
| | | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 71 | 66 | 63 | 60 | 70 | 66 | 63 | 60 | 69 | 65 | 62 | 60 | 68 | 65 | 62 | 60 | 59 |
| | 中 | 0.63 | 0.8 | 76 | 71 | 68 | 66 | 75 | 71 | 68 | 65 | 74 | 70 | 67 | 65 | 72 | 69 | 67 | 65 | 64 |
| | 否 | 0.56 | 1.0 | 79 | 74 | 71 | 69 | 78 | 74 | 71 | 69 | 76 | 73 | 71 | 69 | 75 | 72 | 70 | 68 | 67 |
| 下方投影面積 | 等価発光面積 | cm ² | 1.25 | 81 | 77 | 74 | 72 | 80 | 77 | 74 | 72 | 79 | 76 | 73 | 72 | 77 | 75 | 73 | 71 | 70 |
| | | | 1.5 | 83 | 79 | 77 | 75 | 82 | 79 | 76 | 74 | 80 | 78 | 75 | 74 | 79 | 76 | 75 | 73 | 72 |
| 取付高さ | 器具間隔最大限 | | 2.0 | 85 | 82 | 80 | 78 | 84 | 81 | 79 | 77 | 82 | 80 | 78 | 77 | 81 | 79 | 77 | 76 | 74 |
| | 横方向 (A) | 縦方向 (B) | 2.5 | 86 | 84 | 82 | 80 | 85 | 83 | 81 | 79 | 83 | 82 | 80 | 79 | 82 | 80 | 79 | 78 | 76 |
| Hm | 0.36Hm | 0.36Hm | 3.0 | 87 | 85 | 83 | 81 | 86 | 84 | 82 | 81 | 84 | 83 | 81 | 80 | 83 | 81 | 80 | 79 | 77 |
| | | | 4.0 | 88 | 86 | 85 | 84 | 87 | 86 | 84 | 83 | 85 | 84 | 83 | 82 | 84 | 83 | 82 | 81 | 79 |
| | | | 5.0 | 89 | 87 | 86 | 85 | 88 | 86 | 85 | 84 | 86 | 85 | 84 | 83 | 84 | 83 | 83 | 82 | 80 |
| | | | 7.0 | 90 | 88 | 88 | 87 | 89 | 88 | 87 | 86 | 87 | 86 | 85 | 84 | 85 | 84 | 84 | 83 | 81 |
| | | | 10.0 | 90 | 89 | 89 | 88 | 89 | 88 | 88 | 87 | 87 | 87 | 86 | 86 | 85 | 85 | 85 | 84 | 82 |

