

# 屋内照明器具特性

品番 (品名)	LSEB8045															
光源	LED6200_70_4899 x1 4899.0 lm															
管理番号	K0147596(0)DB1															
BZ分類	BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%	
上方光束	8%	室指数																				
下方光束	92%	照明率 ( X0.01)																				
		ZCM																				
保守率	良 中 否	0.63	0.6	0.56	0.6	54	42	34	29	53	41	34	28	50	39	33	28	47	38	32	27	25
		0.6	0.8	64	52	44	38	62	51	44	38	58	49	42	37	55	47	41	36	34		
		0.56	1.0	71	59	51	45	68	58	51	45	64	56	49	44	61	53	47	43	40		
			1.25	76	66	59	53	74	65	58	52	70	62	56	51	66	59	54	49	46		
下方投影面積	c m <sup>2</sup>	1.5	80	71	64	58	78	70	63	57	74	67	61	56	70	64	59	54	51			
		2.0	86	78	72	66	84	76	70	65	79	73	68	63	75	70	66	62	58			
取付高さ	器具間隔最大限		2.5	90	83	77	72	87	81	75	71	83	77	73	69	79	74	70	67	63		
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	84	79	75	85	81	76	73	81	77	74	71	66		
H m	1.27 H m	1.27 H m	4.0	95	90	86	82	93	89	84	81	89	85	81	78	84	81	78	76	71		
			5.0	97	93	89	86	95	91	88	85	91	88	85	82	87	84	82	79	75		
			7.0	100	97	94	91	98	95	92	89	93	91	89	86	89	87	85	83	79		
			10.0	102	99	97	95	99	97	95	93	95	93	92	90	91	90	88	87	82		

