

屋内照明器具特性

| | | | |
|---------|----------------|----------|--|
| 品番 (品名) | LGB10841 | | |
| 光源 | LLD2020CU1 ×1 | 468.0 lm | |
| 管理番号 | K0179112(0)DR1 | | |
| BZ分類 | BZ1 | | |

| | | | | | | | | | | | | | | | | | | | | |
|------------------|-----------------|---------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率 | 92% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 0% | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 92% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 0.67 | 0.6 | 79 | 74 | 70 | 68 | 78 | 73 | 70 | 68 | 77 | 73 | 70 | 68 | 76 | 72 | 70 | 68 | 67 | |
| | 中 0.63 | 0.8 | 84 | 79 | 76 | 74 | 83 | 79 | 76 | 74 | 82 | 78 | 76 | 74 | 81 | 77 | 75 | 73 | 72 | |
| | 否 0.56 | 1.0 | 87 | 83 | 80 | 78 | 86 | 82 | 80 | 78 | 85 | 82 | 79 | 77 | 83 | 81 | 79 | 77 | 76 | |
| 下方投影面積 等価発光面積 | cm ² | 1.25 | 90 | 86 | 83 | 81 | 89 | 85 | 83 | 81 | 87 | 84 | 82 | 80 | 86 | 83 | 81 | 80 | 79 | |
| | | 1.5 | 91 | 88 | 86 | 84 | 90 | 87 | 85 | 83 | 89 | 86 | 84 | 83 | 87 | 85 | 83 | 82 | 81 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 95 | 92 | 91 | 89 | 94 | 92 | 90 | 88 | 92 | 90 | 89 | 87 | 90 | 89 | 88 | 87 | 85 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 95 | 93 | 92 | 90 | 94 | 93 | 91 | 90 | 93 | 91 | 90 | 89 | 91 | 90 | 89 | 88 | 86 |
| Hm | 0.33Hm | 0.33Hm | 4.0 | 96 | 95 | 94 | 92 | 95 | 94 | 93 | 92 | 94 | 92 | 91 | 91 | 92 | 91 | 90 | 89 | 87 |
| | | | 5.0 | 97 | 96 | 95 | 94 | 96 | 95 | 94 | 93 | 94 | 93 | 92 | 92 | 92 | 92 | 91 | 90 | 88 |
| | | | 7.0 | 98 | 97 | 96 | 95 | 97 | 96 | 95 | 94 | 95 | 94 | 93 | 93 | 93 | 92 | 92 | 91 | 89 |
| | | | 10.0 | 98 | 98 | 97 | 96 | 97 | 97 | 96 | 96 | 95 | 95 | 94 | 94 | 93 | 93 | 93 | 92 | 90 |

