

屋内照明器具特性

品番 (品名)	XLGB1013	
光源	LLD2000VCE1 ×1	531.0 lm
管理番号	K0176325(0)DR1	
BZ分類	BZ5/0.7/BZ4/1.8/BZ5	

器具効率	87%	天井	80%				70%				50%				30%				0%																						
	上方光束 5%		下方光束 82%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																				
				壁	10%				10%				10%				10%				0%																				
床	室指数																				照明率 (X0.01)																				ZCM
保守率	良 中 否	0.67	0.6	4.9	3.9	3.3	2.8	4.8	3.8	3.2	2.8	4.6	3.7	3.2	2.7	4.3	3.6	3.1	2.7	2.5																					
		0.63	0.8	5.8	4.8	4.2	3.7	5.7	4.8	4.1	3.7	5.4	4.6	4.0	3.6	5.1	4.5	4.0	3.6	3.4																					
		0.56	1.0	6.4	5.5	4.8	4.3	6.2	5.4	4.8	4.3	5.9	5.2	4.7	4.2	5.6	5.0	4.6	4.2	3.9																					
			1.25	6.9	6.1	5.4	5.0	6.7	6.0	5.4	4.9	6.4	5.7	5.2	4.8	6.1	5.6	5.1	4.8	4.5																					
下方投影面積	等価発光面積	cm ²	1.5	7.2	6.5	5.9	5.4	7.0	6.3	5.8	5.4	6.7	6.1	5.7	5.3	6.4	5.9	5.5	5.2	4.9																					
			2.0	7.7	7.0	6.5	6.1	7.5	6.9	6.4	6.0	7.1	6.6	6.2	5.9	6.8	6.4	6.1	5.8	5.5																					
取付高さ	器具間隔最大限		2.5	7.9	7.4	6.9	6.5	7.7	7.2	6.8	6.4	7.4	7.0	6.6	6.3	7.1	6.7	6.4	6.1	5.8																					
	横方向 (A)	縦方向 (B)	3.0	8.1	7.6	7.2	6.8	7.9	7.5	7.1	6.7	7.6	7.2	6.9	6.6	7.3	7.0	6.7	6.4	6.1																					
Hm	1.29Hm	1.29Hm	4.0	8.4	8.0	7.6	7.3	8.2	7.8	7.5	7.2	7.9	7.5	7.3	7.0	7.5	7.3	7.0	6.8	6.5																					
			5.0	8.5	8.2	7.9	7.6	8.3	8.0	7.7	7.5	8.0	7.7	7.5	7.3	7.7	7.5	7.3	7.1	6.7																					
			7.0	8.7	8.4	8.2	7.9	8.5	8.3	8.1	7.8	8.2	8.0	7.8	7.6	7.9	7.7	7.6	7.4	7.1																					
			10.0	8.8	8.6	8.4	8.3	8.7	8.5	8.3	8.1	8.4	8.2	8.1	7.9	8.1	7.9	7.8	7.7	7.3																					

