

# 屋内照明器具特性

品番 (品名)	XLGB1633	
光源	LLD2000VCE1 ×1	531.0 lm
管理番号	K0176325(0)DR1	
BZ分類	BZ5/0.7/BZ4/1.8/BZ5	

器具効率	87%	天井	80%				70%				50%				30%				0%																						
	上方光束 5%		下方光束 82%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																				
				壁	10%				10%				10%				10%				0%																				
床	室指数																				照明率 ( X0.01)																				ZCM
保守率	良	0.67	0.6	49	39	33	28	48	38	32	28	46	37	32	27	43	36	31	27	25																					
	中	0.63	0.8	58	48	42	37	57	48	41	37	54	46	40	36	51	45	40	36	34																					
	否	0.56	1.0	64	55	48	43	62	54	48	43	59	52	47	42	56	50	46	42	39																					
			0.56	1.25	69	61	54	50	67	60	54	49	64	57	52	48	61	56	51	48	45																				
下方投影面積	c m <sup>2</sup>		1.5	72	65	59	54	70	63	58	54	67	61	57	53	64	59	55	52	49																					
	等価発光面積		c m <sup>2</sup>	2.0	77	70	65	61	75	69	64	60	71	66	62	59	68	64	61	58	55																				
取付高さ	器具間隔最大限		2.5	79	74	69	65	77	72	68	64	74	70	66	63	71	67	64	61	58																					
	横方向 (A)	縦方向 (B)	3.0	81	76	72	68	79	75	71	67	76	72	69	66	73	70	67	64	61																					
H m	1.29 H m	1.29 H m	4.0	84	80	76	73	82	78	75	72	79	75	73	70	75	73	70	68	65																					
			5.0	85	82	79	76	83	80	77	75	80	77	75	73	77	75	73	71	67																					
			7.0	87	84	82	79	85	83	81	78	82	80	78	76	79	77	76	74	71																					
			10.0	88	86	84	83	87	85	83	81	84	82	81	79	81	79	78	77	73																					

