

屋内照明器具特性

品番 (品名)	LSLG906															
光源	LLD2000LSCE1 ×1 531.0 lm															
管理番号	K0175300(0)DR1															
BZ分類	BZ5/0.7/BZ4															

器具効率	41%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	20%	室指数	照明率 (X0.01)																ZCM		
下方光束	21%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	21	16	13	11	19	15	12	10	16	13	11	9	13	11	9	8	6		
		0.8	24	20	17	15	23	19	16	14	19	16	14	13	16	14	12	11	8		
		1.0	27	23	20	18	25	22	19	17	21	19	17	15	18	16	14	13	10		
		1.25	29	26	23	21	27	24	22	20	23	21	19	17	19	18	16	15	12		
下方投影面積	c m ²	1.5	31	28	25	23	29	26	24	22	25	22	21	19	21	19	18	17	13		
		2.0	33	30	28	26	31	28	26	25	26	25	23	22	22	21	20	19	14		
取付高さ	器具間隔最大限		2.5	34	32	30	29	32	30	28	27	27	26	25	23	23	22	21	20	15	
	横方向 (A)	縦方向 (B)	3.0	35	33	32	30	33	31	30	28	28	27	26	25	24	23	22	21	16	
H m	0.00 H m	1.67 H m	4.0	37	35	34	32	34	33	31	30	29	28	27	26	25	24	23	23	17	
			5.0	37	36	35	34	35	34	33	32	30	29	28	27	25	25	24	24	18	
			7.0	38	37	36	35	36	35	34	33	31	30	29	29	26	25	25	25	18	
			10.0	39	38	37	37	36	35	35	34	31	31	30	30	26	26	26	25	19	

