

# 屋内照明器具特性

品番 (品名)	LGB15337				
光源	LLD4000LCE1 ×1                      845.0 l m				
管理番号	K0176308 ( 0 ) DR 1				
BZ分類	BZ3				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 ( X0.01 )																ZCM	
下方光束	83 %																			
保守率	良 中 否	0.67	0.6	54	46	41	37	53	46	40	37	52	45	40	37	50	44	40	36	35
		0.63	0.8	62	55	49	46	61	54	49	45	59	53	49	45	58	52	48	45	44
			1.0	67	60	55	51	66	60	55	51	64	58	54	51	62	57	54	51	49
		0.56	1.25	71	65	61	57	70	65	60	57	68	63	59	56	66	62	59	56	54
下方投影面積	c m <sup>2</sup>	1.5	74	69	64	61	73	68	64	61	71	67	63	60	69	65	62	60	58	
		2.0	78	73	70	66	77	73	69	66	75	71	68	65	73	70	67	65	63	
取付高さ	器具間隔最大限		2.5	80	76	73	70	79	75	72	70	77	74	71	69	75	72	70	68	66
	横方向 ( A )	縦方向 ( B )	3.0	82	78	75	73	81	77	75	72	78	76	74	71	76	74	72	71	69
H m	1.39 H m	1.39 H m	4.0	84	81	79	77	83	80	78	76	80	78	77	75	78	77	75	74	72
			5.0	85	83	81	79	84	82	80	78	82	80	78	77	80	78	77	76	74
			7.0	86	85	83	82	85	84	82	81	83	82	81	80	81	80	79	78	76
			10.0	87	86	85	84	86	85	84	83	84	83	82	82	82	81	81	80	78

