

屋内照明器具特性

品番 (品名)	LGB15337														
光源	LLD4000MLCE1 ×1 845.0 l m														
管理番号	K0176310(0)DR1														
BZ分類	BZ3														

器具効率	70%	天井	80%				70%				50%				30%				0%		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)															ZCM			
下方光束	70%																				
保守率	良	0.67	0.6	4.6	3.9	3.4	3.1	4.5	3.8	3.4	3.1	4.4	3.8	3.4	3.1	4.2	3.7	3.3	3.1	3.0	
	中	0.63	0.8	5.2	4.6	4.2	3.8	5.2	4.5	4.1	3.8	5.0	4.5	4.1	3.8	4.8	4.4	4.0	3.8	3.7	
	否	0.56	1.0	5.7	5.1	4.7	4.3	5.6	5.0	4.6	4.3	5.4	4.9	4.6	4.3	5.2	4.8	4.5	4.3	4.1	
			1.25	6.0	5.5	5.1	4.8	5.9	5.4	5.1	4.8	5.7	5.3	5.0	4.7	5.6	5.2	4.9	4.7	4.6	
下方投影面積			c m ²																		
等価発光面積			c m ²																		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	1.39 H m	1.39 H m	4.0	7.0	6.8	6.6	6.4	7.0	6.7	6.6	6.4	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.0	
			5.0	7.1	7.0	6.8	6.6	7.1	6.9	6.7	6.6	6.9	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.2	
			7.0	7.3	7.1	7.0	6.9	7.2	7.0	6.9	6.8	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.4	
			10.0	7.3	7.2	7.2	7.1	7.3	7.2	7.1	7.0	7.1	7.0	6.9	6.9	6.9	6.9	6.8	6.7	6.5	

