

屋内照明器具特性	
品番(品名)	LGB15117
光源	LLD40001CQ1 ×1 845.0 lm
管理番号	K0176312(0)DR1
BZ分類	BZ3

器具効率	76%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	76%																																																						
保守率	良 中 否	0.67	0.6	50	42	37	34	49	42	37	34	47	41	37	33	46	40	36	33	32																																			
		0.63	0.8	57	50	45	42	56	49	45	41	54	48	44	41	53	48	44	41	40																																			
			1.0	61	55	50	47	60	55	50	47	59	53	50	47	57	52	49	46	45																																			
		0.56	1.25	65	60	55	52	64	59	55	52	62	58	54	51	61	57	54	51	50																																			
下方投影面積	c m ²	1.5	68	63	59	56	67	62	58	55	65	61	58	55	63	60	57	54	53																																				
		2.0	71	67	64	61	70	66	63	60	68	65	62	60	66	64	61	59	57																																				
等価発光面積	c m ²	2.5	73	70	67	64	72	69	66	64	70	67	65	63	68	66	64	62	60																																				
		3.0	75	72	69	67	74	71	68	66	72	69	67	65	70	68	66	64	63																																				
取付高さ	器具間隔最大限		4.0	76	74	72	70	75	73	71	69	74	72	70	68	72	70	69	67	65																																			
	横方向(A)	縦方向(B)	5.0	78	76	74	72	77	75	73	71	75	73	72	70	73	72	70	69	67																																			
H m	1.39 H m	1.39 H m	7.0	79	77	76	75	78	76	75	74	76	75	74	73	74	73	72	71	69																																			
			10.0	80	79	78	77	79	78	77	76	77	76	75	75	75	74	74	73	71	69																																		

