

屋内照明器具特性

品番 (品名) **LGB15337**

光源 **LLD3020CU1 ×1** **615.0 1m**

管理番号 **K0179074 (0) DR1**

BZ分類 **BZ1**

器具効率	86%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	86%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	74	69	66	64	73	69	66	63	72	68	65	63	71	67	65	63	62	
	中 0.63	0.8	78	74	71	69	78	74	71	69	76	73	70	68	75	72	70	68	67	
	否 0.56	1.0	81	77	74	72	80	77	74	72	79	76	74	72	78	75	73	72	70	
下方投影面積	cm ²	1.25	84	80	78	76	83	80	77	75	81	79	77	75	80	78	76	74	73	
		1.5	85	82	80	78	84	82	79	78	83	80	79	77	81	79	78	76	75	
等価発光面積	cm ²	2.0	87	85	83	81	86	84	82	81	85	83	81	80	83	82	80	79	78	
		2.5	88	86	85	83	88	86	84	83	86	84	83	82	84	83	82	81	79	
取付高さ	器具間隔最大限		3.0	89	87	86	84	88	87	85	84	87	85	84	83	85	84	83	82	80
	横方向 (A)	縦方向 (B)	4.0	90	89	88	86	89	88	87	86	88	86	86	85	86	85	84	83	82
Hm	0.37Hm	0.37Hm	5.0	91	90	89	88	90	89	88	87	88	87	86	86	86	85	84	82	
			7.0	92	91	90	89	91	90	89	88	89	88	87	87	87	86	86	83	
			10.0	92	91	91	90	91	91	90	89	89	89	88	88	87	87	86	84	

