

屋内照明器具特性	
品番 (品名)	NNF 2 2 6 6 6 J
光源	LDL20S.N/11/12-K(960) ×2 960.0 1m
管理番号	K0125017(0)DR1
BZ分類	BZ5/0.7/BZ4

器具効率	93%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.4	4.3	3.6	3.1	5.3	4.3	3.6	3.1	5.1	4.2	3.5	3.1	4.9	4.1	3.5	3.1	2.9
	中	0.77	0.8	6.4	5.4	4.7	4.2	6.3	5.3	4.6	4.2	6.0	5.2	4.6	4.1	5.8	5.1	4.5	4.1	3.9
	否	0.68	1.0	7.0	6.1	5.4	4.9	6.9	6.0	5.4	4.9	6.6	5.9	5.3	4.9	6.4	5.7	5.2	4.8	4.6
			1.25	7.6	6.8	6.1	5.6	7.5	6.7	6.1	5.6	7.2	6.5	6.0	5.6	6.9	6.4	5.9	5.5	5.3
下方投影面積		cm <sup>2</sup>	1.5	8.0	7.2	6.6	6.2	7.8	7.1	6.6	6.1	7.6	7.0	6.5	6.1	7.3	6.8	6.4	6.0	5.8
等価発光面積		cm <sup>2</sup>	2.0	8.5	7.9	7.4	6.9	8.3	7.8	7.3	6.9	8.1	7.6	7.2	6.8	7.8	7.4	7.1	6.7	6.5
取付高さ	器具間隔最大限		2.5	8.8	8.3	7.8	7.4	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	8.1	7.8	7.5	7.2	7.0
	横方向 (A)	縦方向 (B)	3.0	9.0	8.6	8.2	7.8	8.9	8.5	8.1	7.8	8.6	8.3	7.9	7.7	8.4	8.1	7.8	7.6	7.3
1.5m	2.01m	1.93m	4.0	9.3	8.9	8.6	8.3	9.1	8.8	8.5	8.2	8.9	8.6	8.4	8.1	8.7	8.4	8.2	8.0	7.8
2	2.68	2.54	5.0	9.4	9.1	8.9	8.6	9.3	9.0	8.8	8.6	9.1	8.8	8.6	8.4	8.8	8.6	8.5	8.3	8.0
2.5	3.34	3.15	7.0	9.6	9.4	9.2	9.0	9.5	9.3	9.1	8.9	9.3	9.1	8.9	8.8	9.0	8.9	8.8	8.6	8.4
3	4.02	3.76	10.0	9.8	9.6	9.5	9.3	9.6	9.5	9.4	9.2	9.4	9.3	9.2	9.1	9.2	9.1	9.0	8.9	8.6

